

# MATERIAL SAFETY DATA SHEET (MSDS)

R409A

## (Please ensure that this MSDS is received by the appropriate person)

| REF: MS130                           | /ersion:02 | DATE: January 2018                             |  |  |
|--------------------------------------|------------|--|--|--|
| 1 PRODUCT AND COMPANY IDENTIFICATION |            |  |  |  |
| PRODUCT IDENTI                       | FICATION   | 1  |  |  |
| Product Name                         |            | R409A  |  |  |
| Chemical Formula                     |            | CH Cl F2 plus C2 HFH Cl                        |  |  |
|                                      |            | plus, CH3C Cl F2                               |  |  |
| Trade Name                           |            | R409A  |  |  |
| Colour Coding                        |            | Disposable cylinder with a Beige body          |  |  |
| -                                    |            | and the relevant grade stencilled onto         |  |  |
|                                      |            | the cylinder                                   |  |  |
| Valve                                |            | <sup>1</sup> / <sub>4</sub> inch flare fitting |  |  |
| Company Identificati                 | on         | African Oxygen Malawi Limited                  |  |  |
|                                      |            | Johnstone Road, Ginnery Corner                 |  |  |
|                                      |            | Blantyre                                       |  |  |
|                                      |            | Tel. No: +265(1) 871 611                       |  |  |
|                                      |            | Fax No: +265(1) 871 260                        |  |  |
| Emergency No.                        |            | +265 (1) 871 611(24hrs)                        |  |  |

2 COMPOSITION/INFORMATION ON INGREDIENTSChemical Names:A preparation of R22, R124, R142bChemical FamilyMixtures of HalocarbonsUN No.1078ERG No126Hazchem Warning2C non-flammable, non-toxic gas

### **3 HAZARDS IDENTIFICATION**

- Main Hazards. All cylinders are portable gas containers, and must be regarded as pressure vessels at all times.
- Adverse Health effects. Contains a liquefied gas. Contact with liquid may cause frostbite and injury to the cornea. In high concentrations may cause asphyxiation.
- **Chemical hazards.** Heating will cause a rise in pressure with a risk of the cylinders bursting. On combustion, toxic gases are released.
- **Biological hazards.** Contact with liquid could cause frost burns. **Vapour Inhalation.** High exposures may cause an abnormal heart
- rhythm and prove suddenly fatal. May have a narcotic effect, very high concentrations may cause anaesthetic effects and asphyxiation.
- Eye Contact. Vapour unknown effect
- Liquid could cause serious burns

Skin Contact. Vapour - unknown effect

Ingestion. Liquid - see vapour inhalation above

### 4 FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to vaporised R409A. Rescue personnel should be equipped with self-contained breathing apparatus. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be removed to an uncontaminated area and given mouth-to-mouth resuscitation and supplemental oxygen. The use of adrenaline or similar drugs should be avoided.

- **Eye contact.** (Liquid) Rinse with water whilst keeping the eyes wide open for at least 15 minutes. Consult an eye specialist immediately.
- **Skin contact.** (Liquid) Thaw affected areas with water. Remove contaminated clothing and then rinse again with water. If it sticks, do not pull it off. Call a doctor immediately.
- **Ingestion.** Not Specifically applicable (gas). Do not induce vomiting. If patient conscious, wash out mouth with water and give 200 - 300ml water to drink. Obtain immediate medical attention.
- **Inhalation.** Remove patient from exposure, keep warm and at rest. Administer oxygen if necessary. Apply artificial respiration if breathing has ceased or shows signs of failing. In the event of cardiac arrest apply external cardiac massage. Obtain immediate medical attention.

- **Specific hazards.** Pressurised container. On heating there is a risk of bursting due to internal pressure build -up NOT flammable. However, it may present a risk in the event of fire. Toxic vapours (Halogen compounds) are released.
- **Emergency Actions.** Stay upwind. Evacuate the personnel away from the fumes. Cool down the containers/equipment exposed to heat with a water spray.

Protective Clothing. Self-contained breathing apparatus. Safety gloves and shoes, or boots, should be worn when handling cylinders.

Environmental precautions. Prevent the product from spreading into the environment

### 6 ACCIDENTAL RELEASE MEASURES

- **Personal precautions.** Avoid contact with skin and eyes. Do not breathe gas. For further information, refer to 8 "Exposurecontrols/Personal Protection" Heavy vapours. Shut off lowlevel openings in the vicinity (ventilation shafts, drains) Prevent the product from entering cellars, basements or pits. Stop the leak. Ventilate spillage area and basements.
- **Environmental precautions.** Prevent the product from spreading into the environment.

Small spills. Shut off source of product. Ventilate area

Large spills. Evacuate the area. Shut off the source of the spill if this can be done without risk. Restrict access to the area until completion of the clean-up procedure. Ventilate the area using forced-draught if necessary.

### 7 HANDLING AND STORAGE

Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Refer to supplier's container handling instructions. Keep container below  $50^{\circ}$ C in a well ventilated place.

Do not allow cylinders to slide or come into contact with sharp edges. Cylinders should be stacked vertically at all times, and should be firmly secured in order to prevent them from being knocked over. Use a "first in - first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Keep out of reach of children.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- **Occupational exposure hazards.** As R409A is a simple asphyxiant, avoid any areas where spillage has taken place. Only enter once testing has proved the atmosphere to be safe, and remember that the gas is heavier than air.
- **Engineering control measures.** Engineering control measures are preferred to reduce exposures to oxygen depleted atmospheres. General methods include forced-draught ventilation, separate from other exhaust ventilation systems. Ensure that sufficient fresh air enters at, or near, floor level.
- **Personal protection.** Self-contained breathing apparatus should always be worn when entering area where oxygen depletion may have occurred. Safety goggles, gloves and shoes or boots should be worn when handling cylinders.

#### Skin. No known effect.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

| PHYSICAL DATA               |                      |
|-----------------------------|----------------------|
| Chemical Symbol             | Mixture              |
| Boiling point @ 101,325 kPa | -34.2 <sup>0</sup> C |
| Colour                      | colourless           |
| Taste                       | N/A                  |
| Odour                       | Slightly ethereal    |



# R409A (Please ensure that this MSDS is received by the appropriate person)

## 10 STABILITY AND REACTIVITY

- **Conditions to avoid.** The dilution of oxygen concentration in the atmosphere to levels which cannot support life. Never use cylinders as rollers or supports, or for any other purpose than the storing of R409A. Never expose the cylinders to excessive heat, as this may cause sufficient build-up of pressure to rupture the cylinders.
- **Incompatible materials.** Since the performance of plastic materials is affected by polymer variations, compounding agents, fillers, and moulding processes, verify compatibility using actual fabricated parts under end -use conditions.. The effects on specific elastomers depend on the nature of the polymer, the compounding formulation used and the curing of vulcanizing conditions. Actual samples should be tested under end-use conditions before specifying elastomers for critical components.
- Hazardous Decomposition Products. Combustion or thermal decomposition will release toxic gases. (Fluorinated compounds)

# 11 TOXICOLOGICAL INFORMATION

| Acute Toxicity (TWA 8+12 hr)      |                                |
|-----------------------------------|--------------------------------|
| Skin & eye contact                | No known effect                |
| Chronic Toxicity                  | No known effect                |
| Carcinogenicity                   | No known effect                |
| Mutagenicity                      | No known effect                |
| Reproductive Hazards              | No known effect                |
| (For further information see Sect | ion 3. Adverse health effects) |

# 12 ECOLOGICAL INFORMATION

Environmental. Dangerous to the ozone layer.

## 13 DISPOSAL CONSIDERATIONS

**Disposal Methods.** Do not allow the product to be released into the environment. Consult the manufacturer of supplier for information regarding recovery and recycling of the product.

# 14 TRANSPORT INFORMATION

ROAD TRANSPORTATIONUN No.1078ERG No126Hazchem warning2 C Non-flammable gasSEA TRANSPORTATION1078IMDG1078Class2.2LabelNon-flammable gas non toxic gas

## AIR TRANSPORTATION

| ICA | O/IATA Code            | 1078   |
|-----|------------------------|--------|
| Cla | SS                     | 2.2    |
| Pac | kaging instructions    |        |
| -   | Cargo                  | 200    |
| -   | Passenger              | 200    |
| Ma  | ximum quantity allowed |        |
| -   | Cargo                  | 150kgs |
| -   | Passenger              | 75kgs  |

# 15 REGULATORY INFORMATION

EEC Hazard class:Non-flammableNational legislation:OHSact and Regulations 85 of 1993Reference:SANS 10234 and its supplement.

## **16 OTHER INFORMATION**

Bibliography Occupational Exposure Standard (UK HSE EH40)

### EXCLUSION OF LIABILITY

Information contained in this publication is accurate at the date of publication. The company does not accept liability arising from the use of this information, or the use, application, adaptation or process of any products described herein.