

Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

Not for sale in the USA

Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Trade name

CARBON STEEL WELDING WIRES AND RODS

(Afrox MIG 9000 GoldFlo, Afrox MIG 6000/6000 Cert, Afrox TIG 70S-6, Afrox Megapac, Afrox MIG 3000 PLUS, Afrox 250kg ER70S-6 Drum)

Article-no

Product	Diameter	Weight	Winding	Approx.	Item
Packaging	(mm)	(kg)		Length of	Number
Data				Wire/kg (m)	
Afrox MIG	1,0	18	Precision	-	W033972
9000 GoldFlo	(spool-S300)		PLW		
	1,2	18	Precision	-	W033973
	(spool -S300)		PLW		
	1,0 (drum)	250	-	-	W033992
	1,2 (drum)	250	-	-	W033993
MIG 6000	0,8	-	-	245	W033900
	0,9	=	-	186	W033901
	1,0	=	-	160	W033902
	1,2	=	-	110	W033903
	1,6	=	-	63	W033913
TIG 70S-6	1,6	=	-	950	W03050
	2,0	-	-	950	W030502
	2,4	=	-	950	W030503
Afrox	0,9	-	-	-	W033951
Megapac	1,0	=	-	-	W033952
	1,2	=	-	-	W033953
Afrox MIG	0,9	-	-	-	W033931
3000 PLUS	(plastic spool)				
	1,0 (plastic	-	-	-	W033942
	spool)				
	1,2 (plastic	-	-	-	W033943
	spool)				
Afrox 250 kg	1,0	-	-	-	W033962
ER70S-6	(250 kg drum)				
Drum	1,2	-	-	-	W033963
	(250 kg drum)				



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type GMAW/GTAW Un-alloyed steel wire electrodes & Rods Classification: AWS SFA 5.18

Use Gas shielded Arc welding

1.3 Details of the supplier of the safety data sheet

Supplier Afrox

Street address 23 Webber Street, Selby

Johannesburg, 2001

South Africa

Telephone +27 (0) 11 490 0400

Fax +27 (0) 860 020201

Email Customer.service@afrox.linde.com

1.4 Emergency telephone number

Available outside office hours Yes

Emergency phone number 0860 02 02 02

Other

Additional product information Web site: www.afrox.co.za

Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1271/2008 [CLP] applicable

2.2 Label elements

Not applicable

2.3 Other hazards

When the product is used in the welding process the most important hazards are:

Overexposure to fumes and gases from welding can be dangerous to health.

Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire.

Arc rays can injure eyes and burn skin. Electric shock can kill. Avoid touching live electrical parts.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture and please refer to Section 3.2

3.2 Mixtures

AWS Clas's	Fe %	C %	Mn %	Si %	Cu ¹	Ti %	Zr %	AI %
CAS Number	7439-89-6	7440- 44-0	7439-96-5	7440-21-3	7440-50-8	7440- 32-6	7440- 67-7	7429-90-5
ER70S-2	>97	0.07	0.90 to 1.40	0.40 to 0.70	<0.5	0.05 to 0.15	0.02 to 0.12	0.05 to 0.15
ER70S-3	>97	0.06 to 0.15	0.90 to 1.40	0.45 to 0.70	<0.5			
ER70S-4	>97	0.07 to 0.15	1.00 to 1.50	0.65 to 0.85	<0.5			
ER70S-5	>97	0.07 to 0.19	0.90 to 1.40	0.30 to 0.60	<0.5			
ER70S-6	>96	0.07 to 0.15	1.40 to 1.85	0.80 to 1.15	<0.5			
ER70S-7	>96	0.07 to 0.15	1.50 to 2.00	0.50 to 0.80	<0.5			

Section 4. FIRST AND MEASURES

4.1 Description of first aid measures

Inhalation IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms occur.

Skin contact Burns should be treated by a doctor.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Burns from radiation, see doctor.

Ingestion Contact a doctor if more than an insignificant amount has been swallowed.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable

3



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire

with diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not applicable

5.3 Advice for fire fighters

Special protective equipment for

Wear self contained breathing apparatus

fire fighters

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Not applicable

6.4 Reference to other sections

Personal protection see section 8 and for disposal see section 13. Environmental precautions, paragraph 12. See also section 7 Precautions for safe handling.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

welding in a confined space. Wear protective clothing and eye protection appropriate to arc

welding. Remove all flammable materials and liquids before welding.

General hygiene Wash hands before breaks and immediately after handling the product.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s)

Welding process.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Welding fume component	CAS No.	WEL 8hr TWA	STEL 15min TWA
Iron oxide fume (as Fe)	1309-37-1	5	
Manganese and its inorganic compounds (as Mn)	7439-96-5 and others	0.5	
Chromium VI compounds (as Cr)	1333-82-0	0.05	
Chromium III compounds (as Cr)	1308-38-9	0.5	
Nickel and its inorganic compounds Water soluble Water insoluble	1313-99-1	0.1 0.5	
Copper Fume	7440-50-8	0.2	
Nitrogen dioxide	10102-44-0	0.5□	0.95□
Nitrogen monoxide	10102-43-9	0.5□	0.63□
Ozone	10028-15-6		0.2ppm ₉
Carbon dioxide	124-38-9	5000ppm	15000pp m
Carbon monoxide	630-08-0	30ppm	200ppm
Aluminium Inhalable Respirable dust	1344-28-1	10 4	
Zirconium compounds	7440-67-7	5	10

8.2 Exposure controls

Environmental Exposure Controls - refer to Section 6 of this SDS

Technical precaution measures General ventilation and local fume extraction must be adequate to keep fume

concentrations within safe limits.

Eye / face protection Wear eye protection appropriate for welding.

Safety gloves Skin contact should be avoided to prevent possible allergic reactions.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

Other skin protection Wear body protection which helps to prevent injury from radiation, sparks and electric

shock.

Respiratory protection Use respiratory equipment when welding in a confined space. Wear protective clothing

and eye protection appropriate to arc welding.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour Generally grey or coppered coloured when coated

Appearance, physical state Metal wire or Rod

Auto-ignition temperature Not applicable

Auto-inflammability Not auto-flammable

Decomposition temperature Not applicable

Evaporation rate Not applicable
Explosive properties Not explosive

Flammability (solid gas) Not applicable

Flash point Not applicable

Form Fast

Initial boiling point and boiling Not applicable

range

Melting point / Freezing point Not applicable

Odour Odourless

Odour threshold Not applicable

Oxidising properties Not applicable

Partition coefficient: n-octanol / Not applicable

water

pH value Not applicable

Relative density Not applicable

Solubility Not applicable

Solubility in water Insoluble

Upper / lower flammability or Not applicable

explosive limits

Vapour density Not applicable
Vapour pressure Not applicable
Viscosity Not applicable

9.2 Other information



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

Not applicable

Other

Density 7.98g/cm³

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Not applicable

10.2 Chemical stability

Stable at normal conditions.

10.3 Possibility of hazardous reactions

Not applicable

10.4 Conditions to avoid

None under normal conditions

10.5 Incompatible materials

Not applicable

10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material.

Welding fume component	CAS No.	Classification (67/548EEC)	CLP (1272/2008)		Concentration of classified fume components
Aluminium oxide (Al)	1344- 28-1	-	-	-	<0.1
Barium (Ba)	7440- 39-3	-	-	-	<0.1
Bismuth oxide (Bi)	12640- 40-3	-	-	-	<0.1
Calcium (Ca)	1305- 78-8	-	-	-	<0.1 to 0.2
Cobalt oxide (Co)	1307- 96-6	R22: Harmful if swallowed R43: May cause sensitisation by contact	Acute tox 4 (oral) Skin sens. 1	H302 H317	<0.1



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

		R45: May cause	Carc. 1B	H350	<0.1
Chromium III compounds (as Cr)	24613- 89-6	cancer R35: Causes severe burns R43: May cause sensitisation by skin contact	Skin Corr. 1A Skin Sens. 1	H314 H317	
Copper oxide (Cu)	1317- 38-0	-	-	-	0.3 to 1.1
Iron oxide (Fe)	1332- 37-2	-	-	-	45.8 to 61.4
Potassium (K)	7440- 09-7	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Lithium (Li)	7439- 93-2	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Magnesium oxide (Mg)	1309- 48-4	-	-	-	<0.1
Manganese (Mn)	7439- 96-5	-	-	-	6.3 to 15.0
Molybdenum (Mo)	7439- 98-7	Molybdenum trioxide R36/37: Irritating to eyes and respiratory system R40: Limited	Molybdenum trioxide Carc. 2 Eye Irrit. 2 STOT SE 3	H351 H319 H335	<0.1
		evidence of carcinogenic effect			
Sodium (Na)	7440- 23-5	R34: Causes burns	Skin Corr. 1B	H314	<0.1



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

	7440-	R40: Limited evidence of carcinogenic effect R43: May cause sensitisation by skin contact R48/23: Toxic danger of serious damage to health	Carc. 2 Skin sens 1 STOT RE 1	H351 H317 H372	<0.1
Nickel (Ni)	02-0	by prolonged exposure through inhalation R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment			
Lead (Pb)	7439- 92-1	-	-	-	<0.1
Silicon (Si)	7440- 21-3	-	-	-	1.3 to 4.8
Titanium dioxide (Ti)	13463- 67-7	-	-	-	<0.1
Vanadium (V)	7440- 62-2	-	-	-	<0.1
Zinc (Zn)	7440- 66-6	-	-	-	<0.1 to 0.7

Fume analysis: wt %

Al 0.1 max

Ca 0.1 to 0.2

Fe 45.8 t0 61.4

Mn 6.3 to 15

Si 1.3 to 4.8

Zn 0.1 to 0.7

Section 11. TOXICOLOGICAL INFORMATION



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxicology Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary

oedema and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation

of the nose, throat or eyes.

Irritation Not applicable

Corrosive effects Not applicable

Sensitisation May cause sensitisation by skin contact

Mutagenicity Not applicable

Carcinogenicity Welding fumes are possibly carcinogenic to humans

Repeated dose toxicity Not applicable Reproductive toxicity Not applicable

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

12.2 Persistence and degradability

Not applicable

12.3 Bio accumulative potential

Not available

12.4 Mobility in Soil

Not applicable

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects

Not applicable

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

Disposal considerations

Dispose of any product, residue or packing material according to national and local

regulations. Spent ;fume extraction filters shall be disposed of as dangerous waste.

Other

Waste code (EWC) 12 01 13 – welding waste

Section 14. TRANSPORT INFORMATION

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Other

Dangerous goods

Section 15. REGUATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

EU reguations The product does not need to be labelled in accordance with EC directives or respective

national laws.

National regulations EH40/2005 Workplace exposure limits

The Waste Regulations 2011 No. 988

Local laws and regulations should be carefully observed.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05

15.2 Chemical safety assessment

Not applicable

Section 16. OTHER INFORMATION				
References to key literature and	Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH).			
data sources	data sources Regulation (EC) No 1272/2008 of the European Parliament and of the Council.			
	EH40/2005 Workplace exposure limits.			
	The Waste regulations 2011 No.988			
	C&L Inventory database			
	Annex VI CLP Regulation (EC) 1272/2008			
Other				
Manufacturer's notes	Read this Safety Data Sheet carefully and become aware of hazards implied and the safety information.			
	mornadon.			

End of Document



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-02-05