

Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

## Not for sale in the USA

# Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### 1.1 Product identifier

Trade name	CARBON STEEL GAS WELDING RODS Afrox Copper Coated Rod (CCR), Afrox R60				
Article-no	Product Packaging Data	Diameter (mm)	Consumable Length (mm)	Pack Mass (kg)	ltem Number
	(CCR)	1,6 2,5	750 750	5,0 5,0	W000040 W000045
		3,2 5,0	750 750	5,0 5,0	W000041 W000042
	Afrox R60	2,0	-	5,0	W078368

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type Oxy-fuel (Fusion) gas welding Classification: AWS SFA A5.2

Use Oxy-fuel gas welding

1.3 Details of the supplier of the safety data sheet

Supplier	Afrox
Street address	23 Webber Street, Selby
	Johannesburg, 2001
	South Africa
Telephone	+27 (0) 11 490 0400
Fax	+27 (0) 860 020201
Email	Customer.service@afrox.linde.com
1.4 Emergency telephone number	

Available outside office hours	Yes
Emergency phone number	0860 020 202

#### Other

Additional product information Web site: www.afrox.com



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

## Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1271/2008 [CLP] applicable

2.2 Label elements

Not applicable

2.3 Other hazards

When the product is used in the welding process the most important hazards are: Overexposure to fumes and gases from welding can be dangerous to health. Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire. Arc rays can injure eyes and burn skin.

## Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture and please refer to Section 3.2

3.2 Mixtures

AWS <sup>2</sup> Classification	C %	Mn %	Si %	Cu %	Cr %	Ni %	Мо %	AI %
Cas Number	7440-44-0	7439-96-5	7440-21-3	7440-50-8	7440-47-3	7440-02-0	7439-98-7	7429-90-5
R45	0.08	0.05	0.10	0.30	0.20	0.30	0.20	0.02
R60	0.15	0.90 to 1.40	0.10 to 0.35	0.30	0.20	0.30	0.20	0.02
R65	0.15	0.90 to 1.60	0.10 to 0.70	0.30	0.40	0.30	0.20	0.02
R100	0.18 to 0.23	0.70 to 0.90	0.20 to 0.35	0.15	0.40 to 0.60	0.40 to 0.70	0.15 to 0.25	0.02

## Section 4. FIRST AND MEASURES

4.1 Description of first aid measures	
Inhalation	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position
	comfortable for breathing. Call a physician if symptoms occur.
Skin contact	Burns should be treated by a doctor.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing. Burns from radiation, see doctor.
Ingestion	Contact a doctor if more than an insignificant amount has been swallowed.



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable



# Section 5. FIRE-FIGHTING MEASURES

#### 5.1 Extinguishing media

**Suitable extinguishing media** Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire with diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not applicable

5.3 Advice for fire fighters

Special protective equipment for Wear self contained breathing apparatus fire fighters

## Section 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to oxy-fuel gas welding. Skin contact should be avoided to prevent possible allergic reactions.

#### 6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Not applicable

#### 6.4 Reference to other sections

For *Personal protection* see section 8. For *Disposal* see section 13. For *Environmental precautions* see section 12. For *Precautions* for safe handling see 7.1.

## Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions	Ensure adequate ventilation for the welder and others. Use respiratory equipment when
	welding in a confined space. Wear protective clothing and eye protection appropriate to oxy-
	fuel gas welding. Remove all flammable materials and liquids before welding.
General hygiene	Wash hands before breaks and immediately after handling the product.



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

#### 7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

### 7.3 Specific end use(s)

Oxy-fuel gas welding.

# Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Control parameters

Welding fume component	CAS No.	WEL 8hr TWA	STEL 15min TWA	Hazard Classification 67/548/EC	Hazard Classification (GHS) 1272/2008
Iron oxide fume (as Fe)	1309-37-1	5	10		
					H332/H302
Manganese and its inorganic compounds (as Mn)	7439-96-5	0.5		R20/R22	Acute Tox.4
Nickel and its inorganic compounds					H351 Carc.2
Water soluble	7440-02-0	0.1		R40/R43	H317skin sens 1/
Water insoluble		0.5		R49/R53	H413 Aquatic Ch.4
Silica, amorphous					
(total inhalable dust)	-	6			
(respirable dust)		2.4			
Carbon Dioxide	124-38-9	5000ppm	15000ppm		
Carbon Monoxide	630-08-0	30ppm	200ppm		

#### 8.2 Exposure controls

Environmental Exposure Controls

Refer to Section 6 of the SDS

	General ventilation and local fume extraction must be adequate to keep fume
	concentrations within safe limits.
Eye / face protection	Wear eye protection appropriate for welding.
Safety gloves	Skin contact should be avoided to prevent possible allergic reactions.
Other skin protection	Wear body protection which helps to prevent injury from radiation, sparks and electric
	shock.
Respiratory protection	Use respiratory equipment when welding in a confined space. Wear protective clothing
	and eye protection appropriate to arc welding.



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

## Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and c	hemical properties
Appearance, colour	Generally copper coloured.
Appearance, physical state	Metal solid rod
Auto-ignition temperature	Not applicable
Auto-inflammability	Not auto-flammable
Decomposition temperature	Not applicable
Evaporation rate	Not applicable
Explosive properties	Not explosive
Flammability (solid gas)	Not applicable
Flash point	Not applicable
Form	Fast
Initial boiling point and boiling	Not applicable
range	
Melting point / Freezing point	Not applicable
Odour	Odourless
Odour threshold	Not applicable
Oxidising properties	Not applicable
Partition coefficient: n-octanol /	Not applicable
water	
pH value	Not applicable
Relative density	Not applicable
Solubility	Not applicable
Solubility in water	Insoluble
Upper / lower flammability or	Not applicable
explosive limits	
Vapour density	Not applicable
Vapour pressure	Not applicable
Viscosity	Not applicable

9.2 Other information

Not applicable

Other

Density 7.98g/cm<sup>3</sup>

## Section 10. STABILITY AND REACTIVITY



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

 10.1 Reactivity
 Not applicable

 10.2 Chemical stability
 Stable at normal conditions.

 10.3 Possibility of hazardous reactions
 Not applicable

 10.4 Conditions to avoid
 Not applicable

None under normal conditions

10.5 Incompatible materials

Not applicable

#### 10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material.

Welding fume component	CAS No.	Classification (67/548EEC)	CLP (1272/2	2008)	Concentration of classified fume components
Aluminium oxide (Al)	1344-28-1	-	-	-	<0.1
Barium (Ba)	7440-39-3	-	-	-	<0.1
Bismuth oxide (Bi)	12640-40-3	-	-	-	<0.1
Calcium (Ca)	1305-78-8	-	-	-	<0.1 to 0.2
Cobalt oxide (Co)	1307-96-6	R22: Harmful if swallowed R43: May cause	Acute tox 4 (oral) Skin sens. 1	H302 H317	<0.1
Chromium III compounds (as Cr)	24613-89-6	sensitisation by contact R45: May cause cancer R35: Causes severe burns R43: May cause sensitisation by skin contact	Carc. 1B Skin Corr. 1A Skin Sens. 1	H350 H314 H317	<0.1
Copper oxide (Cu)	1317-38-0	-	-	-	0.3 to 1.1
Iron oxide (Fe)	1332-37-2	-	-	-	45.8 to 61.4
Potassium (K)	7440-09-7	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Lithium (Li)	7439-93-2	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Magnesium oxide (Mg)	1309-48-4	-	-	-	<0.1



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

Manganese (Mn)	7439-96-5	-	-	-	6.3 to 15.0
Molybdenum (Mo)	7439-98-7	Molybdenum trioxide R36/37: Irritating to eyes and respiratory system	Molybdenum trioxide Carc. 2	H351 H319	<0.1
		R40: Limited evidence of carcinogenic effect	Eye Irrit. 2 STOT SE 3	H335	
Sodium (Na)	7440-23-5	R34: Causes burns	Skin Corr. 1B	H314	<0.1
		R40: Limited evidence of	Carc. 2	H351	<0.1
Nickel (Ni)	<ul> <li>R43: May sensitisati contact</li> <li>R48/23: T</li> <li>R48/23: T</li> <li>serious da by prolon through in</li> <li>R52/53: F</li> <li>aquatic or cause long effects in</li> </ul>	carcinogenic effect R43: May cause sensitisation by skin contact	Skin sens 1	H317	
			STOT RE 1	H372	
		R48/23: Toxic danger of serious damage to health by prolonged exposure through inhalation			
		R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment			
Lead (Pb)	7439-92-1	-	-	-	<0.1
Silicon (Si)	7440-21-3	-	-	-	1.3 to 4.8
Titanium dioxide (Ti)	13463-67-7	-	-	-	<0.1
Vanadium (V)	7440-62-2	-	-	-	<0.1
Zinc (Zn)	7440-66-6	-	-	-	<0.1 to 0.7

Classification information relates to the fume during use

# Section 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxicology Excessive

Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary oedema and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation of the nose, throat or eyes.

Irritation Not applicable



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

Corrosive effects	Not applicable
Sensitisation	May cause sensitisation by skin contact
Mutagenicity	Not applicable
Carcinogenicity	Welding fumes are possibly carcinogenic to humans
Repeated dose toxicity	Not applicable
Reproductive toxicity	Not applicable

## Section 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere.

12.2 Persistence and degradabilit	У
	Not applicable
12.3 Bio accumulative potential	
	Not applicable
12.4 Mobility in Soil	
	Not applicable
12.5 Results of PBT and vPvB as	sessment
	Not applicable
12.6 Other adverse effects	
	Net en elle else

Not applicable

# Section 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

**Disposal considerations** Dispose of any product, residue or packing material according to national and local regulations. Spent ;fume extraction filters shall be disposed of as dangerous waste.

#### Other

Waste code (EWC) 12 01 13 – welding waste

# Section 14. TRANSPORT INFORMATION

14.1 UN number

Not applicable



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

14.2 UN proper shipping name	Not applicable	
14.3 Transport hazard class(es)	Not applicable	
14.4 Packing group	Not applicable	
14.5 Environmental hazards	Not applicable	
14.6 Special precautions for user	Not applicable	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable		

Other

Dangerous goods No

# Section 15. REGUATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

EU regulations	The product does not need to be labelled in accordance with EC directives or respective
	national laws.
National regulations	EH40/2005 Workplace exposure limits
	The Waste Regulations 2011 No. 988
	Local laws and regulations should be carefully observed.

15.2 Chemical safety assessment

Not applicable

## Section 16. OTHER INFORMATION

 References to key literature and
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH).

 data sources
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council.

 EH40/2005 Workplace exposure limits.
 The Waste regulations 2011 No.988



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-03-24

	C&L Inventory database Annex VI CLP Regulation (EC) 1272/2008
Other	
Manufacturer's notes	Read this Safety Data Sheet carefully and become aware of hazards implied and the safety information.

End of Document